



DMDVR20 LBST

L-Band Satellite Modem



HIGHLIGHTS

MODULATOR

- ▶ IESS-309/310/314/315 compliant Satellite Modulator
- ▶ 950 to 2050 MHz L-Band Operation, 1 Hz Steps
- ▶ BPSK/QPSK/OQPSK/8-PSK/16-QAM modulation
- ▶ 2.4 Kbps to 20 Mbps, 1 bps Steps
- ▶ Forward Error Correction (FEC) – Viterbi, Reed-Solomon, Trellis, Turbo Product Code
- ▶ Integrated 10 MHz high-stability BUC reference
- ▶ Optional 24 or 48 VDC for up to 10 W BUC

DEMODULATOR

- ▶ Configurable for unframed clear channel serial data transmission for Telco grade hub & spoke services
- ▶ Supports MCPC/SCPC networks using industry standard LDPC
- ▶ 950 to 2150 MHz L-Band operation, 1 Hz Steps
- ▶ QPSK/8-PSK/16-APSK demodulation
- ▶ 2.0 Mbps to 20 Mbps, 1 bps Steps
- ▶ Industry standard forward error correction LDPC+BCH
- ▶ LNB Power: 18 VDC \pm 0.5 V (350 mA max)

OVERVIEW

The DMDVR20 LBST is based on the proven design and technology of the DMD20 Universal Satellite Modem and the DD240 professional grade MCPC satellite demodulator with industry leading reliability.

The DMDVR20 LBST is ideal for high quality private networks requiring low latency and low jitter transmission. With its ability to support asymmetrical link operation with IESS compliant transmission and LDPC reception, the DMDVR20 LBST can receive large shared TDM carriers and provide small to medium sized return carriers for data/voice/video applications in a hub and spoke environment. DMDVR20 LBST is one of the most advanced remote site terminals in a single one rack unit size.

The DMDVR20 LBST's impressive remote management capability surpasses all others in the field. It can be remotely monitored and controlled via the trusted RLLP (Radyne Link Level Protocol) or through the RS-232 Terminal port.

Supported by an extensive line of redundancy switches, converters, encoders and decoders, the DMDVR20 LBST can be integrated into any network compatible with the MD2401 Quad Demodulator and the DM240XR Broadcast modulator.

Hardware Options

- Turbo FEC (Transmit)
- 48 VDC Input Power
- High-Stability Reference
- BUC/LNB Power

Software Options

- Data Rate Upgrades
- 8-PSK (Modulator/ Demodulator)
- 16-QAM (Modulator)
- 16-APSK (Demodulator)

Interface Options:

- RS-530/422 Serial

APPLICATIONS

- Hub Spoke Networks for Data/Voice/Video

DMDVR20 L-Band Satellite Modem

SPECIFICATIONS

Modulator

Modulation:	BPSK, QPSK, and OQPSK (8-PSK, 8-QAM & 16-QAM Optional)
L-Band Tuning Range:	950 to 2050 MHz in 1 Hz Steps
Impedance:	50 Ohm
Connector:	Female Type N
Return Loss:	10 dB Minimum
Output Power:	0 to -25 dBm
Output Accuracy:	±1.0 dB Over Frequency and Temperature
Output Spectrum:	Meets IESS-308/309/310 Power Spectral Mask
Spurious:	-55 dBc In-Band -45 dBc Out-of-Band
Harmonics:	-45 dBc
On/Off Power Ratio:	>60 dB
Data Rate Range:	2.4 kbps to 20 Mbps in 1 bps steps
Scrambler:	CCITT V.35 (Others Optional)
FEC:	Viterbi, K=7 at 1/2, 3/4 and 7/8 Trellis 2/3
	Turbo Product Code (Optional) Per IESS-315 BPSK 21/44 QPSK/OQPSK 1/2, 3/4, 7/8 8-PSK/16-QAM 3/4, 7/8
Outer Encoder Options:	Reed-Solomon INTELSAT Custom (N,K) Reed-Solomon (Optional)
Data Clock Source:	Internal, External, RX Recovered
Internal Stability:	5 x 10 ⁻⁸
BUC DC Voltage:	BUC 24 V @ 3.5 A Maximum BUC 48 V @ 2.8 A Maximum (Optional)
BUC Reference:	10 MHz, 3 dBm ± 3 dB

Monitor and Control

Remote:	RS-485/RS-232 Selectable
Terminal	RS-232

Demodulator

Demodulation:	QPSK, (8-PSK, 16-APSK Optional)
L-Band Tuning Range:	950 to 2150 MHz in 1 Hz Steps
Impedance:	75 Ohm
Connector:	Type F Female
Return Loss:	7 dB Minimum
Spectrum:	ETSI EN 302 307 Compliant
Input Level:	-60 to -25 dBm
Composite Power	<-20 dBm total Input Power
FEC:	LDPC Concatenated BCH Per ETSI EN 302 307
Normal Blocks:	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9 and 9/10
Short Blocks:	1/2, 3/5, 2/3, 3/4, 4/5, 5/6 and 8/9
Decoder Options:	Per ETSI EN 302 307
Descrambler:	Per ETSI EN 302 307
Acquisition Range:	Programmable
LNB DC voltage	13, 15, 18, 20 Selectable

Demodulation/FEC	Code Rate	Data Rate Range
QPSK LDPC+BCH	1/2	2.0 Mbps - 20.0 Mbps
QPSK LDPC+BCH	3/5	2.4 Mbps - 20.0 Mbps
QPSK LDPC+BCH	2/3	2.6 Mbps - 20.0 Mbps
QPSK LDPC+BCH	3/4	3.0 Mbps - 20.0 Mbps
QPSK LDPC+BCH	4/5	3.1 Mbps - 20.0 Mbps
QPSK LDPC+BCH	5/6	3.2 Mbps - 20.0 Mbps
QPSK LDPC+BCH	8/9	3.5 Mbps - 20.0 Mbps
QPSK LDPC+BCH	9/10	3.6 Mbps - 20.0 Mbps
8-PSK LDPC+BCH	3/5	3.5 Mbps - 20.0 Mbps
8-PSK LDPC+BCH	2/3	3.9 Mbps - 20.0 Mbps
8-PSK LDPC+BCH	3/4	4.3 Mbps - 20.0 Mbps
8-PSK LDPC+BCH	5/6	4.8 Mbps - 20.0 Mbps
8-PSK LDPC+BCH	8/9	5.2 Mbps - 20.0 Mbps
8-PSK LDPC+BCH	9/10	5.4 Mbps - 20.0 Mbps
16-APSK LDPC+BCH	2/3	5.1 Mbps - 20.0 Mbps
16-APSK LDPC+BCH	3/4	5.7 Mbps - 20.0 Mbps
16-APSK LDPC+BCH	4/5	6.0 Mbps - 20.0 Mbps
16-APSK LDPC+BCH	5/6	6.4 Mbps - 20.0 Mbps
16-APSK LDPC+BCH	8/9	6.9 Mbps - 20.0 Mbps
16-APSK LDPC+BCH	9/10	7.2 Mbps - 20.0 Mbps

Environmental

Prime Power:	100 to 240 VAC, 50 to 60 Hz, 150 W Maximum with 10 W BUC
Operating Temperature:	0 to 50°C, 95% Humidity, Non-Condensing
Storage Temperature:	-20 to -70°C, 99% Humidity, Non-Condensing

Physical

Dimensions: (height x width x depth)	19" x 19.25" x 1.75" in. (48.26 cm x 48.89 cm x 4.45 cm)
Weight:	8.5 Pounds (3.83 Kg)



2114 West 7th Street, Tempe, Arizona 85281 USA Voice 1 480 333 2200 Fax 1 480 333 2540 Email sales@comtechefdata.com

Comtech EF Data reserves the right to change specifications of products described in this document at any time without notice and without obligation to notify any person of such changes. Information in this document may differ from that published in other Comtech EF Data documents. Refer to the website or contact Customer Service for the latest released product information.