



SkyWire™ MDX240

Satellite Network Gateway



HIGHLIGHTS

- ▶ Most bandwidth efficient TDMA solution available
- ▶ Connect remote sites in a TRUE full mesh, hub and spoke, or hybrid network configuration
- ▶ TDMA network throughput capability of over 86 Mbps and 168,000 pps
- ▶ Multiple Link / Multiple Transponder Operation
- ▶ Advanced Turbo Product Code FEC
- ▶ Dynamic bandwidth allocation with single hop bandwidth-on-demand functionality
- ▶ Programmable, multi-queued Quality of Service(QoS)
- ▶ Graphical user interface program for monitor and control

OVERVIEW

The revolutionary SkyWire™ MDX420 is one of the most innovative satellite products in years. The system combines the throughput and robustness of a single channel per carrier (SCPC) system with the bandwidth savings of a time division multiple access (TDMA) system.

The SkyWire MDX420 leverages the benefits of each to provide the ultimate in satellite network performance.

The SkyWire MDX420 is the first TDMA broadband satellite system to eliminate the need for high stability references or an expensive central hub with complicated system software. With its revolutionary single hop bandwidth-on-demand capability, the SkyWire MDX420 minimizes system response time to changes in traffic flow. The small efficient burst sizes

and ultra low overhead allow the SkyWire MDX420 to provide unprecedented bandwidth efficiency and increased network throughput.

The SkyWire MDX420 system is easy to configure and the auto-everything 10/100/1000 terrestrial data ports provide instant connectivity for any IP application.

Whether you need a TRUE full mesh, a hub and spoke, or a hybrid combination, the SkyWire MDX420 system provides the most cost-effective, easy to use, bandwidth efficient solution available today. And, the system is packaged in a single, secure, one rack unit box.

USERS & APPLICATIONS

Typical users of the SkyWire MDX420 are oil and gas, mining, satellite news gathering operators, enterprises, and military. Common applications are:

- IP Centric Applications
- Full Mesh Data and Voice
- Bandwidth on Demand Video, Voice and IP
- Communications on the Move / Halt
- SNG Comms and Video over IP

SkyWire™ MDX240 Satellite Network Gateway

SPECIFICATIONS

The published specifications reflect the maximum SkyWire MDX420 performance. Each SkyWire MDX420 can be configured to customer requirements via hardware / software options applied at the factory or in the field.

SkyWire MDX420 Performance

Acquisition Performance	Modulation & TPC FEC	User Data Rate Range	Network Threshold	Typical BER 1E-8
Enhanced	QPSK .710	328k - 12.7m	2.9dB	3.5dB
Enhanced	QPSK .793	366k - 14.2m	3.3dB	3.8dB
Standard	QPSK .793	378k - 14.7m	3.4dB	4.4dB
Enhanced	8PSK .793	537k - 20.9m	6.5dB	7.6dB
Standard	8PSK .793	555k - 21.6m	7.8dB	9.0dB

Modulator

Modulation:	QPSK (8PSK Optional)
L-Band Tuning Range:	950 to 1750 MHz in 1 Hz Steps
Impedance:	50 Ohm
Connector:	N-Type (50 Ohm)
Return Loss:	10 dB Minimum
Output Power:	0 to -25 dBm
Output Accuracy:	±1.0 dB Over Frequency and Temperature
Spurious:	-55 dBc In-Band -45 dBc Out-of-Band
Harmonics:	-45 dBc
On/Off Power Ratio:	>60 dB
Symbol Rate Range	.256 to 10 Msps in 1 sps steps
FEC:	Turbo Product Code .710, .793
Internal Stability:	±280 ppB ±50 ppB (Optional)
Optional BUC Power:	3.3 Amps @ 24 V Maximum 2.8 Amps @ 48 V Maximum
BUC Reference:	10 MHz, +3 dBm ± 3 dB

Demodulator

Demodulation:	QPSK (8PSK Optional)
L-Band Tuning Range:	950 to 2050 MHz in 1 Hz Steps
Impedance:	75 Ohm
Connector:	F-Type (75 Ohm) Female
Return Loss:	10 dB Minimum
Input Level:	10 x Log (Symbol Rate) -122 + 12 dB
Total Input Power:	-10 dBm or +40 dBc (the lesser)
Symbol Rate Range	.256 to 10 Msps in 1 sps steps
FEC:	Turbo Product Code .710, .793
Carrier Acquisition Range:	± 5% of the Symbol Rate
LNB DC Power:	500 mA @ 24 VDC Maximum
LNB Reference:	10 MHz, +3 dBm ± 3 dB

Monitor and Control

Ethernet 10/100 Base-T
SNMP V1, V2, and V3
MIB Browser
Radyne Network Configuration GUI

Service Port

Terminal RS-232

Terrestrial Interface

Ethernet 10/100/1000 Base-T

Alarms

One Form-C Relay
Five Open Collector

Environmental

Prime Power: 100 to 240 VAC, 50 to 60 Hz,
Auto-sensing
40 Watts Max, Gateway only
200 Watts Max, BUC & LNB Powered

Operating Temperature: 0 to 50° C, 95% Humidity, Non-Condensing

Storage Temperature: -20 to 70° C, 99% Humidity, Non-Condensing

Physical

Size: 19"W x 13"D x 1.75"H
(48.26 x 33.0 x 4.45 cm)

Weight: 7 pounds (3.17 kg)



2114 West 7th Street, Tempe, Arizona 85281 USA Voice 1 480 333 2200 Fax 1 480 333 2540 Email sales@comtechefdata.com

Comtech EF Data reserves the right to change specifications of products described in this document at any time without notice and without obligation to notify any person of such changes. Information in this document may differ from that published in other Comtech EF Data documents. Refer to the website or contact Customer Service for the latest released product information.

France Telecom - TDF - Groupe des écoles des telecommunications Turbo codes patents license.