

High-End Modems	Frequency	Data Rate	FEC	Modulation	Other
DM240XR Digital Video Broadcast Modulator	50 – 90 MHz 100 – 180 MHz 950 – 2050 MHz	1 – 238 Mbps & 1 – 68 Msps (DVB-S & DVB-DSNG) 1 – 190 Mbps & 1 – 45 Msps (DVB-S2)	<ul style="list-style-type: none"> • Viterbi Reed-Solomon • LDPC/BCH 	<ul style="list-style-type: none"> • QPSK • 8-PSK • 16-APSK • 16-QAM • 32-APSK 	<ul style="list-style-type: none"> • DVB-S, DVB-DSNG, DVB-S2 • CCM, ACM & VCM Modes • AutoEQ™ Uplink Equalization • Two Data Interface Slots (PIIC)
DVC240XR – DVB/DVBS2 Modulator Card	50 – 90 MHz & 100 – 180 MHz 950 – 2050 MHz (L-Band Version)	1 – 238 Mbps 1-68 Msps (DVB-S) 1 – 190 Mbps 1 – 45 Msps (DVB-S2)	<ul style="list-style-type: none"> • Viterbi Reed-Solomon • LDPC/BCH 	<ul style="list-style-type: none"> • QPSK • 8-PSK • 16-APSK • 16-QAM • 32-APSK 	<ul style="list-style-type: none"> • DVB-S, DVB-DSNG, DVB-S2 • Modulator on a Card
CDM-750 Advanced High-Speed Trunking Modem	50 – 180 MHz 950 – 2150 MHz (L-Band Version)	1 – 169 Mbps 1 – 63 Msps	<ul style="list-style-type: none"> • DVB-S2 • LDPC/BCH 	<ul style="list-style-type: none"> • QPSK • 8-PSK • 16-APSK • 32-APSK 	<ul style="list-style-type: none"> • DVB-S2 • ACM • DoubleTalk® Carrier-in-Carrier® • Gigabit Ethernet • Two Data Interface Slots (PIIC): (OPT) G.703 T3/E3
DVR240XR – DVB/DVBS2 Demodulator Card	950 – 2150 MHz	2 – 160 Mbps 2 – 45 Msps (DVB-S2) 2 – 145 Mbps 2 – 45 Msps (DVB-S)	<ul style="list-style-type: none"> • Viterbi Reed-Solomon (RX) • LDPC/BCH (RX) 	<ul style="list-style-type: none"> • QPSK • 8-PSK • 16-APSK • 16-QAM 	<ul style="list-style-type: none"> • Demodulator on a Card • DVB-S, DVB-DSNG, DVB-S2
DD240XR Digital Video Broadcast Demodulator	50 – 90 MHz 100 – 180 MHz 950 – 2150 MHz	2 – 160 Mbps & 2 – 45 Msps (DVB-S2) 2 – 144 Mbps & 2 – 45 Msps (DVB-S)	<ul style="list-style-type: none"> • Viterbi Reed-Solomon • LDPC/BCH 	<ul style="list-style-type: none"> • QPSK • 8-PSK • 16-APSK • 16-QAM 	<ul style="list-style-type: none"> • DVB-S, DVB-DSNG, DVB-S2 • Upgrades via PCMCIA
SLM-5650A Satellite Modem	52 – 88 MHz 104 – 176 MHz 950 – 2000 MHz	64 kbps – 155 Mbps (Gigabit Ethernet) 64 kbps – 51.84 Mbps (HSSI) 64 kbps – 20 Mbps (EIA-530 / RS-422)	<ul style="list-style-type: none"> • TPC • Viterbi • Reed-Solomon • Trellis • Sequential 	<ul style="list-style-type: none"> • BPSK • QPSK • OQPSK • 8-PSK • 16-QAM 	<ul style="list-style-type: none"> • MIL-188-165A • AES-256 TRANSEC • Vipersat dSCPC • Gigabit Ethernet Network Processor with IP QoS • G.703 • LVDS • DoubleTalk® Carrier-in-Carrier®
CDM-700 High Speed Satellite Modem	52 – 88 MHz 104 – 176 MHz 950 – 1950 MHz (L-Band H/W Option)	1.5 – 155 Mbps 1 – 64 Msps	<ul style="list-style-type: none"> • TPC 	<ul style="list-style-type: none"> • QPSK • 8-PSK • 16-QAM • 64-QAM 	<ul style="list-style-type: none"> • Two data Interface Slots • Dual G.703 (E3, T3, STS-1) • OC3/STM-1 • Gigabit Ethernet • HSSI
CDM-710 Broadcast Satellite Modem	52 – 88 MHz 104 – 176 MHz 950 – 2000 MHz (L-Band H/W Option)	0.49 – 124.6 Mbps 1 – 45 Msps	<ul style="list-style-type: none"> • Viterbi Reed-Solomon • LDPC/BCH 	<ul style="list-style-type: none"> • QPSK • 8-PSK • 16-APSK • 32-APSK • 16-QAM 	<ul style="list-style-type: none"> • DVB-S, DVB-DSNG, DVB-S2 • ASI • HSSI • Gigabit Ethernet
CDM-710G High-Speed Satellite Modem	52 – 88 MHz 104 – 176 MHz 950 – 1950 MHz (L-Band H/W Option)	0.49 – 124.6 Mbps 1 – 45 Msps	<ul style="list-style-type: none"> • LDPC/BCH 	<ul style="list-style-type: none"> • QPSK • 8-PSK • 16-APSK • 32-APSK 	<ul style="list-style-type: none"> • DVB-S, DVB-DSNG, DVB-S2 • HSSI • Gigabit Ethernet • G.703 (E3, T3, STS-1)

High-End Modems	Frequency	Data Rate	FEC	Modulation	Other
DMD2050 MIL-STD-188-165A Compliant Universal Satellite Modem	70 ± 18 MHz & 140 ± 36 MHz IF 1350 ± 400 MHz & 1500 ± 500 MHz L-Band	2.4 kbps – 52 Mbps	<ul style="list-style-type: none"> • Viterbi • Reed-Solomon • Sequential • Trellis • TPC • LDPC 	<ul style="list-style-type: none"> • BPSK • QPSK • OQPSK • 8-PSK • 16-QAM 	<ul style="list-style-type: none"> • MIL-STD-188-165A • IESS-308/309/310/314/315 • DVB-S • G.703 with Drop & Insert • RS-422, HSSI, ASI • Gigabit Ethernet • DoubleTalk® Carrier-in-Carrier®
DMD50 Universal Satellite Modem	50 – 90 MHz & 100 – 180 MHz IF 950 – 2050 MHz L-Band	2.4 kbps – 52 Mbps	<ul style="list-style-type: none"> • Viterbi • Reed-Solomon • Sequential • Trellis • TPC 	<ul style="list-style-type: none"> • BPSK • QPSK • OQPSK • 8-PSK • 16-QAM 	<ul style="list-style-type: none"> • Dual Band Capability • IESS-308/309/310/314/315 • DVB-S • G.703 T1/E1/T2/E2/T3/E3/STS1 • Drop & Insert • 4-port 10/100Base-T Ethernet • RS-422, HSSI, ASI • Gigabit Ethernet
Mid-Range Modems	Frequency	Data Rate	FEC	Modulation	Other
CDM-625 Advanced Satellite Modem	50 – 180 MHz (Standard) 950 – 2000 MHz (L-Band S/W Option) Dual band capability with Independent TX & RX	18 kbps – 25 Mbps	<ul style="list-style-type: none"> • VersaFEC® • LDPC • TPC • Viterbi • TCM • Reed-Solomon • Sequential 	<ul style="list-style-type: none"> • BPSK • QPSK • OQPSK • 8-PSK • 8-QAM • 16-QAM 	<ul style="list-style-type: none"> • DoubleTalk® Carrier-in-Carrier® • ACM • 4-port Managed Ethernet Switch with VLAN & QoS • Quad E1 Drop & Insert • IP Sub Mux • CDM-600 Emulation Mode • Open Network Support
CDM-Qx & CDM-QxL Multi-Channel Satellite Modems	50 – 90 MHz 100 – 180 MHz 950 – 1950 MHz (L-Band Version)	32 kbps – 20 Mbps	<ul style="list-style-type: none"> • TPC • Viterbi • TCM • Reed-Solomon 	<ul style="list-style-type: none"> • BPSK • QPSK • 8-PSK • 16-QAM 	<ul style="list-style-type: none"> • DoubleTalk® Carrier-in-Carrier® • Quad E1 with Drop & Insert
CDM-600 & CDM-600L Satellite Modems	50 – 90 MHz 100 – 180 MHz 950 – 2000 MHz (L-Band Version)	2.4 kbps – 20 Mbps	<ul style="list-style-type: none"> • LDPC • TPC • Viterbi • Sequential • TCM • Reed-Solomon 	<ul style="list-style-type: none"> • BPSK • QPSK • OQPSK • 8-PSK • 8-QAM • 16-QAM 	<ul style="list-style-type: none"> • Drop & Insert
DMD20 Universal Satellite Modem	50 – 90 MHz & 100 – 180 MHz IF 950 – 2050 MHz L-Band	2.4 kbps – 20 Mbps	<ul style="list-style-type: none"> • Viterbi • Reed-Solomon • Sequential • Trellis • TPC • LDPC 	<ul style="list-style-type: none"> • BPSK • QPSK • OQPSK • 8-PSK • 8-QAM • 16-QAM 	<ul style="list-style-type: none"> • Dual Band Capability • IESS-308/309/310/314/315 • DVB-S • G.703 T1/E1/T2/E2 • Drop & Insert • 4-port 10/100Base-T Ethernet • Gigabit Ethernet
DMD20 LBST L-Band Satellite Modem and ODU Driver	950 – 2050 MHz	2.4 kbps – 20 Mbps	<ul style="list-style-type: none"> • Viterbi • Reed-Solomon • Sequential • Trellis • TPC • LDPC 	<ul style="list-style-type: none"> • BPSK • QPSK • OQPSK • 8-PSK • 8-QAM • 16-QAM 	<ul style="list-style-type: none"> • IESS-308/309/310/314/315 • DVB-S • G.703 T1/E1/T2/E2 • Drop & Insert • 4-port 10/100Base-T Ethernet • Gigabit Ethernet • 10 MHz Reference for BUC & LNB • DC Power for BUC & LNB

Mid-Range Modems	Frequency	Data Rate	FEC	Modulation	Other
DMDVR20 LBST L-Band Satellite Modem	950 – 2050 MHz (Modulator)	2.4 kbps – 20 Mbps (Modulator)	<u>Modulator</u> • Viterbi • Reed-Solomon	<u>Modulator</u> • BPSK • QPSK • OQPSK • 8-PSK • 16-QAM	<u>Modulator</u> • IESS-309/310/314/315 • DC Power for BUC
	950 – 2150 MHz (Demodulator)	2.0 Mbps – 20 Mbps (Demodulator)	• Trellis • TPC <u>Demodulator</u> • LDPC-BCH	<u>Demodulator</u> • QPSK • 8-PSK • 16-APSK	<u>Demodulator</u> • Normal Block and Short Block FEC • DC Power for LNB <u>Data Interface</u> • RS-422
OM-20 Rugged Antenna Mount Modem	950 – 2050 MHz	2.4 kbps – 20 Mbps	• Viterbi • Reed-Solomon • Sequential • Trellis • TPC	• BPSK • QPSK • OQPSK • 8-PSK • 16-QAM	• Outdoor, Weatherproof Chassis • IESS-308/309/310/314/315 • DVB-S • 10/100Base-T Ethernet • RS-422 • G.703 T1/E1 with Drop & Insert
DMD1050 L-Band Satellite Modem Board	950 – 2050 MHz	2.4 kbps – 20 Mbps	• Viterbi • Reed-Solomon • Sequential • Trellis • TPC	• BPSK • QPSK • OQPSK • 8-PSK • 16-QAM	• Modem on a Compact PCB Daughter Card • MIL-STD-188-165A • IESS-308/309/310/314/315 • DVB-S • RS-422 / Gigabit Ethernet • 10 MHz Reference
Entry-Level Modems	Frequency	Data Rate	FEC	Modulation	Other
CDM-570/L, CDM-570/L-IP & CDM-570/L-IPEN Satellite Modems	50 – 90 MHz 100 – 180 MHz	2.4 kbps – 9.98 Mbps	• TPC • Viterbi • TCM • Reed-Solomon	• BPSK • QPSK • OQPSK • 8-PSK • 8-QAM • 16-QAM	• IP, IP with encryption & Standard Models Available • E1 RAN Optimization (Option)
	950 – 2000 MHz (L-Band Version)				
CDD-564/L & CDD-564/LEN Quad IP Demodulators	50 – 90 MHz 100 – 180 MHz	16 kbps – 9.98 Mbps	• TPC	• BPSK • QPSK • 8-PSK • 8-QAM • 16-QAM	• Integrated IP Module • Optional Encryption Models
	950 – 1950 MHz (L-Band Version)				
CDD-562L & CDD-562LEN Dual IP Demodulators	950 – 1950 MHz	16 kbps – 9.98 Mbps	• TPC	• BPSK • QPSK • 8-PSK • 8-QAM • 16-QAM	• Integrated IP Module • Optional Encryption Model

	DM240XR	DVC240XR	CDM-750	DVR240XR	DD240XR	SLM-5650A	CDM-700	CDM-710	CDM-710G	DMD2050	DMD50	CDM-625	CDM-Qx & CDM-QxL	CDM-600 & CDM-600L	DMD20	DMD20 LBST	DMDVR20 LBST	OM-20	DMD1050	CDM-570/L, CDM-570/L-IP & CDM-570/L-IPEN	CDD-564/L & CDD-564/LEN	CDD-562L & CDD-562LEN	
Broadband Interactive Services	X	X		X	X		X	X	X														
Broadcast Content Distribution	X	X		X	X			X															
Cellular Backhaul												X	X	X	X	X					X		
Communications at-the-Pause						X				X									X				
Communications on-the-Move						X						X							X	X	X	X	
Digital Cinema	X	X		X	X			X															
Digital Signage	X	X		X	X			X															
Direct To Home	X	X		X	X			X															
Disaster Recovery & Emergency Communications	X	X	X	X	X		X		X												X	X	X
Enterprise	X	X		X	X		X	X	X			X									X	X	X
Flyaway Communications										X									X				
G.703 Trunking	X		X		X		X		X		X	X	X	X	X	X	X						
High Speed Content Delivery	X	X	X	X	X		X		X														
Integrated Satellite Terminal Communications										X									X				
IP Trunking	X		X		X		X		X		X	X			X	X							
IPTV / Business Television	X						X	X															
Offshore & Maritime Communications												X	X								X	X	X
Rugged Environments						X																	
Satellite News Gathering	X	X		X	X			X				X									X	X	X
Secure Networks						X																	
Shelterless Deployments																		X					

Comtech EF Data reserves the right to change specifications of products described in this document at any time without notice and without obligation to notify any person of such changes. Information in this document may differ from that published in other Comtech EF Data documents. Refer to the website or contact Customer Service for the latest released product information.
© February 2010 Comtech EF Data