Modem Accessories



Overview

The STS11 (70/140 MHz) and STS11L (L-Band) Solid-State Transfer Switch provides simple IF or L-Band switching for the DM240XR Modulators. The straightforward design and easy access to connectors and LEDs allow for ease of use. The STS11/STS11L is designed for installation in any convenient location (with the included brackets). The STS11 and STS11L offer a highly reliable and simple to use IF or L-Band switching for use with video or data applications where simultaneous and redundant data paths are being switched in a chain switching environment.

Features

- Simple IF or L-Band switching for DM240XR Modulators
- Easy access to connectors and LEDs •
- Small size makes installation easy and convenient with included brackets •

Specifications

General Specifications

Modulator only
50 msec maximum
BNC, 75 Ohms
SMA, 50 Ohms (optional)
DB-9 male
DB-9 male
20 dB
14 dB

Power and Environmental

	Prime Power	+12 VDC provided to the unit through prime and backup cabling from the modulator	
	Operating	0 to 50°C, 95% humidity,	
	Temperature	non-condensing	
	Storage	-20 to 70°C, 99% humidity,	
	Temperature	non-condensing	

Physical

Dimensions	1.75" x 4.4" x 3.4"
(height x width x depth)	(4.45 x 11.18 x 8.63 cm)
Weight	0.5 lbs (0.22 kg)



2114 West 7th Street, Tempe, Arizona 85281 USA Voice: +1.480.333.2200 • Fax: +1.480.333.2540 • Email: sales@comtechefdata.com

See all of Comtech EF Data's Patents and Patents Pending at http://patents.comtechefdata.com Comtech EF Data reserves the right to change specifications of products described in this document at any time without notice and without obligation to notify any person of such changes. Information in this document may differ from that published in other Comtech EF Data documents. Refer to the website or contact Customer Service for the latest released product information © 2018 Comtech EF Data 1/4/2018