

Overview

The CDM-425 Advanced Satellite Modem continues to build on our legacy of providing the most efficient and reliable satellite modems. It offers the most popular and powerful features of the CDM-625A, with a smaller footprint and less power. Its Forward Error Correction options comprise 18 VersaFEC® ModCods and 74 VersaFEC-2 ModCods, permitting the user to optimize for latency and coding gain for any link budget. It includes DoubleTalk® Carrier-in-Carrier® bandwidth compression, additional TX rolloffs and sophisticated packet processing capabilities. This combination of advanced technologies enables multi-dimensional optimization, allowing satellite communications users to:

- Minimize operating expenses (OPEX)
- Maximize throughput without using additional transponder resources
- Maximize availability (margin) without using additional transponder resources
- Minimize capital expenses (CAPEX) by allowing a smaller BUC/HPA and/or antenna
- Or, a combination to meet specific business needs

Features

- DoubleTalk Carrier-in-Carrier bandwidth compression
- Carrier-in-Carrier Automatic Power Control
- VersaFEC-2 High Performance LDPC with Adaptive Coding and Modulation (ACM), Short Block and Long Block – similar performance to DVB-S2X with significantly lower latency.
- VersaFEC FEC with Adaptive Coding and Modulation (ACM), both standard and Ultra-Low Latency (ULL)
- 5%, 10%, 15%, 20%, 25% and 35% Transmit Filter Rolloff
- Optional Packet Processor with header compression, payload compression, advanced Quality of Service (QoS) and Managed Switch Mode with VLAN support
- Integrated 4-port managed Ethernet switch with VLAN and QoS
- Jumbo frame support
- Dual Band Capability: 70/140 MHz and extended L-Band (950 – 2250 MHz) in same unit
- Data Rate: 18 kbps to 25 Mbps
- Symbol Rate: 18 ksps to 12.5 Msps
- Modulation: BPSK, QPSK, 8-QAM/8-ARY, 16-QAM/16-ARY, 32-ARY
- FEC: VersaFEC (low-latency LDPC) and VersaFEC-2 (high performance LDPC)

Typical Users

- Mobile Network Operators
- Telecom Operators
- Satellite Service Providers
- Enterprise
- Offshore

Common Applications

- Mobile Backhaul
- Offshore & Maritime Communications
- Enterprise
- Wide Range of data interfaces: EIA-422/530, V.35, G.703 T1/E1, Quad G.703 E1, 4-port 10/100Base-T Ethernet
- IEEE 1588v2 Precision Time Protocol
- Sub Mux to multiplex IP/Ethernet traffic with serial or G.703 traffic
- Drop & insert for T1/E1
- Enhanced D&I++ for single T1/E1 & quad E1
- Management: 10/100Base-T Ethernet with SNMP, Distant End SNMP Proxy, HTTP, Telnet and EIA-232/EIA-485
- RADIUS Client
- ETSI compliant Carrier ID using MetaCarrier® Technology
- Embedded Distant-end Monitor and Control (EDMAC)
- Automatic Uplink Power Control (AUPC), and combined AUPC and ACM
- Standard high-stability internal reference (± 6 x 10-8)
- L-Band TX: 10 MHz reference for BUC, FSK communications and optional BUC power supply
- L-Band RX: 10 MHz reference and LNB power supply
- L-Band: Advanced FSK for LPOD M&C
- 1:1 and 1:10 redundancy switches available
- Backwards compatible with CDM-625 (VersaFEC modes) and CDM-625A (VersaFEC and VersaFEC-2 modes)




Doubletalk Carrier-in-Carrier

DoubleTalk Carrier-in-Carrier, based on patented "Adaptive Cancellation" technology, allows transmit and receive carriers of a duplex link to share the same transponder bandwidth. DoubleTalk Carrier-in-Carrier is complementary to all advances in modem technology, including advanced FEC and modulation techniques. As these technologies approach theoretical limits of power and bandwidth efficiencies, DoubleTalk Carrier-in-Carrier utilizing advanced signal processing techniques provides a new dimension in bandwidth efficiency.

Figure 1 shows the typical full-duplex satellite link, where the two carriers are adjacent to each other.

Figure 2 shows the typical DoubleTalk Carrier-in-Carrier operation, where the two carriers are overlapping, thus sharing the same spectrum.



RL -45.80 dBn
ATTEN 10 dB
5.80 dB.010

Carrier 1

U10E0 BANDHIDTH
188 Hz

Carrier 2

CENTER 78.888 MHz
RB 21.5 kHz *UB 188 Hz

SPAN 2.888 MHz
ST 2.791 sec

Figure 1

Figure 2

When observed on a spectrum analyzer, only the Composite is visible. Carrier 1 and Carrier 2 are shown in Figure 2 for reference only.

As DoubleTalk Carrier-in-Carrier allows equivalent spectral efficiency using a lower order modulation and/or code rate, it can reduce the power required to close the link thereby reducing CAPEX by allowing a smaller BUC/Amplifier and/or antenna. Alternatively, DoubleTalk Carrier-in-Carrier can be used to achieve very high spectral efficiencies E.g., DoubleTalk Carrier-in-Carrier when used with 16-ARY modulation approaches the bandwidth efficiency of 256-ARY (8 bps/Hz).

When combined with VersaFEC-2 or VersaFEC and optimized transmit filter rolloff, it can provide unprecedented savings in transponder bandwidth and power utilization. This allows for its successful deployment in bandwidth-limited and power-limited scenarios, as well as reduction in earth station BUC/HPA power requirements.

Carrier-in-Carrier® is a Registered Trademark of Comtech EF Data DoubleTalk® is a Registered Trademark of Raytheon Applied Signal Technology VersaFEC® is a Registered Trademark of Comtech EF Data

Carrier-in-Carrier Automatic Power Control (CnC-APC)

The patent-pending Carrier-in-Carrier Automatic Power Control (CnC-APC) mechanism enables modems on both sides of a CnC link to automatically measure and compensate for rain fade while maintaining the Total Composite Power. In addition to automatically compensating for rain fade, CnC-APC also enables the modems to share link margin, i.e. a modem in clear sky conditions can effectively transfer excess link margin to a distant end modem experiencing fade, thereby further enhancing overall availability.

VersaFEC-2 High Performance LDPC Forward Error Correction

CDM-425 offers a new high performance LDPC FEC specifically design to optimize performance at low and mid-tier symbol rates. VersaFEC-2 long-block provides 38 ModCods (BPSK to 32-ARY) with performance generally comparable with DVB-S2X at significantly lower latency and short-block provides 36 ModCods (BPSK to 32-ARY) with higher coding gain than first generation VersaFEC and similar latency. All higher order constellations are circular or quasi-circular for optimal peak-to-average performance. Both CCM and ACM operation is support for long block and short block.

VersaFEC Forward Error Correction

CDM-425 offers VersaFEC, a system of high-performance short-block LDPC codes designed to provide maximum coding gain while minimizing latency. VersaFEC is designed to support ACM and CCM mode of operation

The Ultra Low Latency (ULL) codes provide even lower latency compared to standard VersaFEC codes.

Adaptive Coding & Modulation (ACM)

Satellite users have traditionally relied on worst case link margin to overcome rain fade which leads to significant inefficiencies. ACM can provide significant increase in throughput as well as availability. ACM converts the fade margin into increased capacity making it possible to more than double the throughput for Ku-band operation. Even under deep fade, ACM may be able to maintain the link at the lower ModCod thereby increasing availability. It is tightly integrated with packet processor QoS which allows higher priority, mission critical traffic to be maintained even during fade.

Dual Band Capability

CDM-425 supports 70/140 MHz and extended L-Band (950 – 2250 MHz) capability in the same unit with independently selectable transmit and receive IF. This simplifies sparing and stocking in networks requiring 70/140 MHz and L-Band units.

4-Port Managed Ethernet Switch with VLAN & QoS

CDM-425 incorporates a 4-port 10/100Base-T managed Ethernet switch with VLAN capability and priority-based Quality of Service. Access (Native) Mode and Trunk Mode are supported. Traffic can be prioritized using port-based priority or VLAN priority. The modem supports jumbo frames with maximum Ethernet frame size of 2048 bytes.

Packet Processor

The optional high-performance Packet Processor enables efficient IP networking and transport over satellite with low overhead encapsulation, header compression, payload compression and advance Quality of Service to the CDM-425. The QoS combined with header and payload compression ensures the highest quality of service with minimal jitter and latency for real-time traffic, priority treatment of mission critical applications and maximum bandwidth efficiency.

Packet processor supports Routed mode as well as Managed Switch Mode of operation. In managed switch mode, it operates as a layer 2 switch with VLAN support, enabling seamless integration with existing infrastructure while providing full optimization including low overhead Streamline Encapsulation, header compression and payload compression and advanced QoS.

Header Compression

The Packet Processor incorporates industry-leading header compression for Ethernet and IP traffic. In managed switch mode, header compression can reduce the 54 byte Ethernet/IP/UDP/RTP header to as little as 1 byte. For TCP/IP, the 54 byte header (including Ethernet) is reduced to as little as 3 bytes. For applications such as VoIP, header compression can provide bandwidth savings exceeding 65%. E.g. the 8 kbps G.729 voice codec requires 31.2 kbps once encapsulated into an Ethernet frame with IP/UDP/RTP. With header compression, the same voice call needs about 9 kbps – a saving of almost 70%. And, bandwidth requirements for typical Web/HTTP traffic can be reduced by 10% or more with TCP/IP header compression.

Payload Compression

The Packet Processor incorporates industry-leading GZIP based payload compression for IP/Ethernet traffic. Implemented in hardware for maximum throughput and efficiency, payload compression can typically reduce the required satellite bandwidth by 30-40%.

Streamline Encapsulation (SLE)

The Packet Processor incorporates Comtech EF Data's patent-pending low overhead Streamline Encapsulation (SLE). SLE can reduce the encapsulation overhead by as much as 65% compared to industry standard HDLC.

Advanced Quality of Service (QoS)

The Packet Processor incorporates multi-level QoS to ensure the highest quality service with minimal jitter and latency for real-time traffic, priority treatment of mission critical applications and maximum bandwidth efficiency. Supported modes are:

- DiffServ Industry-standard method of providing QoS enabling seamless co-existence in networks that implement DiffServ
- Max/Priority Provides traffic prioritization with the ability to limit maximum traffic per priority class
- Min/Max Provides a Committed Information Rate (CIR) to each user defined class of traffic with the ability to allow a higher burstable rate depending on availability

A powerful classifier supports packet classification by Protocol, VLAN ID / range, ToS Byte, Source IP (or subnet), Destination IP (or subnet), Source Port (or Range), Destination Port (or Range) and DSCP (for DiffServ).

Quad E1 Interface (QDI) with Enhanced D&I++

The CDM-425 supports a Quad E1 interface that can aggregate up to four full or fractional E1s into a single carrier, with very low overhead. This provides significant CAPEX savings by reducing the number of modems and could possibly reduce the BUC/HPA size by eliminating the multi-carrier backoff. A proprietary, closed network drop & insert (D&I++) allows for dropping or inserting any combination of 1 to 31 time slots on each E1. D&I++ is supported for E1-CCS only.

IP Sub Multiplexer

The IP sub mux allows multiplexing IP/Ethernet traffic with serial or G.703 traffic into a single carrier. This is particularly useful for cellular backhaul when both E1 and IP backhaul is required. This reduces the number of modems and could possibly reduce the BUC/HPA size by eliminating the multi-carrier backoff. The IP sub mux ratio ranges from 9:1 (IP data rate is 9 times that of the serial or G.703 data rate) to as low as 1:59. IP sub mux can also be used to provision an overhead IP channel for management when using non IP/Ethernet traffic interfaces.

EDMAC & AUPC

The CDM-425 supports EDMAC, EDMAC-2, EDMAC-3 and AUPC. EDMAC/EDMAC-2/EDMAC-3 can be used to monitor and control the distant end of a satellite link using a proprietary overhead channel. EDMAC-3 is also used for SNMP management of the distant end modem. AUPC automatically adjusts modem transmit power based on feedback from the distant end modem to maintain the desired Eb/No. AUPC and EDMAC are supported for point-to-point duplex links. Simultaneous AUPC and ACM is offered for IP modes.

Management & SNMP Proxy

The modem can be managed via the front panel, the remote M&C port (EIA-232/EIA-485), or the 10/100Base-T Ethernet port. With support for SNMP, HTTP and Telnet, the modem can be easily integrated into an IP-based management system.

The CDM-425 can also act as SNMP proxy for the distant end CDM-425. This allows distant end CDM-425 management using SNMP without requiring an end-to-end IP link.

RADIUS Client

The CDM-425 supports the Remote Authentication Dial In User Service (RADIUS) client enabling centralized user authentication for management access to the modem by web browser and telnet. RADIUS client supports Password Authentication Protocol (PAP) and Challenge-Handshake Authentication Protocol (CHAP).

IEEE 1588v2 Precision Time Protocol (PTP)

PTP has emerged as the key technology for frequency, time and phase synchronization over a packet network. The CDM-425 incorporates hardware support for PTP, thereby significantly improving synchronization accuracy for satellite backhaul.

Advanced FSK for LPOD Monitoring & Control

The Advanced FSK allows for monitoring and control of LPOD through modern front panel menus, serial remote control and Telnet.

Specifications

Specification	ns — — — — — — — — — — — — — — — — — — —
Data Rate	18 kbps to 25 Mbps, in 1 bps steps
	(modulation, FEC & data interface dependant)
Symbol Rate	18 ksps to 12.5 Msps
Operating	950 – 2250 MHz (standard)
Frequency	50 – 180 MHz (option)
	100 Hz resolution, independent TX and RX operation
Major Operating	VersaFEC and VersaFEC-2 Codec with Adaptive Coding and
Modes	Modulation (ACM) or Constant Coding & Modulation (CCM)
(See User Manual	EDMAC Framed with/without AUPC
for Details)	Drop & insert (D&I) /Enhanced D&I++ (option)
	Quad E1 drop & insert (QDI) (option)
	DoubleTalk Carrier-in-Carrier (option)
FEC & Modulation	
VersaFEC Codec	BPSK Rate 0.488
	QPSK Rate 0.533, 0.631, 0.706, 0.803
	8-QAM Rate 0.576 (ECCM), 0.642, 0.711, 0.780
	16-QAM Rate 0.644 (ECCM), 0.731, 0.780, 0.829, 0.853
	BPSK 0.493 (ULL)
	QPSK 0.493, 0.654, 0.734 (ULL)
VersaFEC-2	Long Block:
Codec	BPSK Rate 0,489
	QPSK Rate 0.489, 0.537, 0.586, 0.611, 0.635, 0.660, 0.684,
	0.733
	8-ARY Rate 0.521, 0.537, 0.562, 0.586, 0.611, 0.635, 0.660,
	0.684, 0.708, 0.733
	16-ARY Rate 0.586, 0.611, 0.635, 0.660, 0.684, 0.708, 0.733,
	0.757, 0.782
	32-ARY Rate 0.660, 0.684, 0.708, 0.733, 0.757, 0.782, 0.801,
	0.831, 0.855, 0.879
	Short Block:
	BPSK Rate 0,489
	QPSK Rate 0,469 QPSK Rate 0.489, 0.537, 0.586, 0.611, 0.635, 0.660, 0.684,
	0.733
	8-ARY Rate 0.521, 0.537, 0.562, 0.586, 0.611, 0.635, 0.660,
	0.684, 0.708, 0.733
	16-ARY Rate 0.586, 0.611, 0.635, 0.660, 0.684, 0.708, 0.733,
	0.757, 0.782
	32-ARY Rate 0.660, 0.684, 0.708, 0.733, 0.757, 0.782, 0.801,
	0.831
Scrambling	ITU V.35 (Intelsat variant)/ IESS-315
Management	10/100Base-T Ethernet with SNMP, HTTP and Telnet
Managomont	support, EIA-232, EIA-485 (2- or 4-wire)
Form C Relays	Hardware fault. RX and TX traffic alarms
External	BNC connector
Reference	Input: 1, 2, 5, or 10 MHz, -6 dBm to
(Input OR Output)	$+10 \text{ dBm}$, 50 $\Omega/75 \Omega$ (nominal)
(mpai On Output)	1 10 apm, 30 22/13 22 (nonlinal)
	Output: 10 MHz, 2.7 V peak-to-peak
	± 0.4 V, low impedance output
	1 ± 0 v, low impedance output

Data Interfaces

Data interfaces	
EIA-422/-530 DCE, Up to 14 Mbps	OF nin Davik (famala)
V.35 DCE, Up to 14 Mbps	25-pin D-sub (female)
G.703 T1, 1.544 Mbps	0 -i- D (6
(Balanced 100 Ω)	9-pin D-sub (female)
G.703 E1, 2.048 Mbps	BNC (female)
(Unbalanced 75 Ω or balanced 120 Ω)	BNC (remaie)
Additional 2.048 Mbps E1 Ports for Quad-E1	Onin Daub (famala)
(Balanced 120 Ω)	9-pin D-sub (female)
Modem Alarms	15-pin D-sub (male)
4-port 10/100Base-T Managed Ethernet Switch (Optional Packet Processor Available)	4 x RJ-45

$\Lambda \Lambda$	ndı	เปล	40	r

Frequency Stability	± 0.06 ppm (± 6 x 10 ⁻⁸), 0° to 50°C (32° to
	122°F) with internal reference
Transmit Filtering	Alpha = 35%, per IESS-308
Additional Alphas (Rolloff)	5%, 10%, 15%, 20% and 25%
Harmonics and Spurious	Better than -60 dBc/4 kHz
	(typically <-65 dBc/4kHz)
	Measured from 1 to 500 MHz
	(50-180 MHz band)
	Measured F ₀ ± 500 MHz
Transmit On/Off Ratio	(950-2250 MHz band) -60 dBc minimum
	< 0.48° rms double sided, 100 Hz to 1 MHz
Output Phase Noise	(Minimum 16 dB better overall than the Intelsat
	IESS-308/309 requirements)
	dB/Hz Frequency Offset
	-63.0 100 Hz
	-73.0 1 kHz
	-83.0 10 kHz
	-93.0 100 kHz
	Fundamental AC line spurious is -42 dBc or lower
	The sum of all other single sideband spurious, from
	0 to 0.75 x symbol rate, is -48 dBc or lower
Output Power	50-180 MHz:
	0 to -25 dBm, 0.1 dB steps
	'
	950-2250 MHz:
	0 to -40 dBm, 0.1 dB steps
Power Accuracy	50-180 MHz:
	± 0.5 dB over frequency, data rate, modulation type
	and temperature range of 15 to 35° C
	± 0.8 dB over frequency, data rate, modulation type
	and temperature range of 0 to 50° C
	950-2250 MHz:
	± 0.5 dB over frequency, data rate, modulation type
	and temperature range of 15 to 35° C
	± 0.7 dB over frequency, data rate, modulation type
Output Impadance 9	and temperature range of 0 to 50° C
Output Impedance & Return Loss	50-180 MHz: 50 Ω/75 Ω, 16 dB minimum return loss
Return Loss	(18 dB typical), BNC connector
	950-2250 MHz: 50 Ω, 18 dB minimum return loss
	(21 dB typical), Type-N connector
Clocking Options	Internal, ± 0.06 ppm (SCT)
Clocking Options	External, locking over a ± 100 ppm range (TT)
	Loop timing (RX satellite clock) – supports
	asymmetric operation
	External clock
External TX Carrier Off	By TTL 'low' signal or external contact closure
BUC Reference	Via TX IF center conductor, 10.0 MHz
	± 0.06 ppm (with internal reference), selectable
(1() MHz)	
(10 MHz)	on/off, 0.0 dBm ± 3 dB
<u> </u>	on/off, 0.0 dBm ± 3 dB 24 VDC, 4.17 Amps max., 90 W @ 50° C
BUC Power Supply	24 VDC, 4.17 Amps max., 90 W @ 50° C
<u> </u>	
BUC Power Supply	24 VDC, 4.17 Amps max., 90 W @ 50° C 48 VDC, 3.125 Amps max., 150 W @ 50° C

Demodulator	
Input Power Range,	50-180 MHz: -105 + 10 log (symbol rate) to
Desired Carrier	-70 + 10 log (symbol rate) dBm
	950-2250 MHz: -130 + 10 log (symbol rate) to -80 + 10 log (symbol rate) dBm
Max Composite Operating	50-180 MHz and 950-2250 MHz:
Level	For symbol rates < 224 ksps, ≥ 47 dBc
	For symbol rates ≥ 224 ksps,
	99 – 10 log (symbol rate, desired carrier) dBc,
	+10 dBm max., with the additional requirement that
	within ± 10 MHz of the desired carrier the composite
	power is ≤ +30 dBc
Absolute Maximum	+20 dBm
Acquisition Range	Programmable in 1kHz increments
Below 64 ksymbols/sec	± 1 kHz to ± (Rs/2) kHz, where Rs = symbol rate in ksymbols/sec
Between 64 and 389 ksymbols/sec	± 1 kHz to ± 32 kHz

		E.g. 120 ms average at 64 kbps, R1/2 QPSK, ± 10 kHz acquisition sweep range, 6 dB Eb/No
	Plesiochronous/	Selectable from 64 to 262,144 bits, in 16-bit steps
	Doppler Buffer	(Additional limitations for G.704 frame boundaries)
	Receive Clock	RX satellite, TX terrestrial, external reference
	Clock Tracking	± 100 ppm minimum
	LNB Reference (10 MHz)	Via RX IF center conductor, 10.0 MHz ± 0.06 ppm (with internal reference), selectable on/off, -3.0 dBm ± 3 dB
	LNB Voltage	Selectable on/off, 13 VDC, 18 VDC per DiSEq 4.2 at 500 mA maximum
	Monitor Functions	E _b /N ₀ estimate, corrected BER, frequency offset, buffer fill state, receive signal level

 \pm 1 kHz to \pm (0.1 * Rs) kHz, up to a maximum of

Highly dependent on data rate, FEC rate, and

demodulator acquisition range.

DoubleTalk Carrier-in-Carrier

Above 389 ksymbols/sec

Acquisition Time

Double Laik Callier-III-Cal	illei
Delay Range	0 to 330 ms
Power Spectral Density Ratio	BSPK/QPSK/8PSK/8-QAM: -7 dB to
(Interferer to Desired)	+11 dB
	16-QAM/16-ARY, 32-ARY: -7 dB to +7 dB
Maximum Symbol Rate Ratio	3:1 (TX:RX or RX:TX)
Eb/No Degradation	0 dB Power Spectral Density Ratio BPSK/QPSK/OQPSK: 0.3 dB 8-QAM: 0.4 dB 8-SK: 0.5 dB 8-ARY: 0.4 dB 16-QAM: 0.6 dB 16-ARY; 0.6 dB 32-ARY: 0.6 dB
Satellite Restrictions	+10 dB power spectral density ratio Additional 0.3 dB Satellite in "loop-back" mode (i.e., the transmit station can receive itself) "Non-processing" satellite (i.e., does not demodulate or remodulate the signal)

Available Options

, aa	· opaciic
Hardware	100 – 240 VAC, 120 W AC primary power supply
Hardware	-48 VDC, 125 W primary power supply
Hardware	24 VDC, 90 W @ 50°C BUC power supply, AC, 24 VDC or 48 VDC
	primary power supply
Hardware	48 VDC, 150 W @ 50°C (180 W @ 30°C) BUC power supply, AC or
	48 VDC primary power supply
Hardware	Packet Processor
FAST	70/140 MHz (in addition to L-Band IF)
FAST	8-QAM/8-ARY modulation
FAST	16-QAM/16-ARY modulation
FAST	32-ARY modulation
FAST	Activate DoubleTalk Carrier-in-Carrier Feature
FAST	DoubleTalk Carrier-in-Carrier Data Rate (full) - 512 kbps, 1.1 Mbps,
	2.5 Mbps, 5 Mbps, 10 Mbps, 15 Mbps, 20 Mbps or 25 Mbps
FAST	DoubleTalk Carrier-in-Carrier Data Rate (fractional) – 2.5 Mbps,
	5 Mbps, 10 Mbps, 15 Mbps, 20 Mbps or 25 Mbps
FAST	D&I / D&I++ for single Port T1/E1
FAST	D&I++ For Quad E1 Port 2, 3 and 4
FAST	Quality of Service (requires Packet Processor)
FAST	Header Compression (requires Packet Processor)
FAST	Payload Compression (requires Packet processor)
FAST	Advanced Network Timing (IEEE 1588v2 PTP)
FAST	Carrier ID
FAST	VersaFEC Codec data rate (CCM) – 2.5 Mbps, 5 Mbps, 16 Mbps
FAST	VersaFEC Codec symbol rate (ACM) – 1.2 Msps, 4.1 Msps
FAST	VersaFEC-2 Codec data rate (CCM) – 10 Mbps, 15 Mbps, 20 Mbps or 25 Mbps
FAST	VersaFEC-2 Codec symbol rate (ACM) – 2.0 Msps, 4.1 Msps, 8.0 Msps or 12.5 Msps

Accessories

Accessories		
CRS-170A	1:1 Modem Redundancy Switch (L-Band)	
CRS-180	1:1 Modem Redundancy Switch (70/140 MHz)	
CRS-300	1:10 Modem Redundancy Switch (Not available with Packet Processor)	
CRS-280	1:10 IF Redundancy Switch (70/140 MHz)	
CRS-280L	1:10 IF Redundancy Switch (L-Band)	
CRS-500	1:N Modem Redundancy System (For use with Packet Processor Only)	
CRS-282XXX	1:10 IF Redundancy Switch (For use with CRS-500)	

Environmental and Physical

	0 1 01 5000 (001 10005)
Temperature	Operating: 0 to 50°C (32 to 122°F)
	Storage: -40 to 85°C (-40 to 185°F)
Humidity	95% maximum, non-condensing
Power Supply	100 – 240 VAC, +6%/-10%, 50/60 Hz, auto sensing
	-48 VDC (HW option)
Dimensions (1RU)	1.75" x 19.0" x 14"
(height x width x depth)	(4.4 x 48 x 35.5 cm) approximately
Weight	8.8 lbs (3.9 kg) maximum, with Packet Processor
_	module and 48 VDC BUC power supply installed
CE Mark	EN 301 489-1 (ERM)
	EN55022 (Emissions)
	EN55024 (Immunity)
	EN 61000-3-2
	EN 61000-3-3
	EN60950 (Safety)
FCC	FCC Part 15, Subpart B



2114 West 7th Street, Tempe, Arizona 85281 USA

Voice: +1.480.333.2200 • Fax: +1.480.333.2540 • Email: sales@comtechefdata.com